

NFX GOLD INC.	MAXIMUS VENTURES LTD.
55 Adelaide Street East, Suite 410 Toronto, ON M5C 1K6 Canada Tel: (416) 360-8006 Fax: (416) 361-1333	Operations: 37 Wynwood Road, Chatham, NJ 07928 USA Tel: (973) 635-8262 Fax: (973) 635-4991 Admin: 202 – 837 W. Hastings St., Vancouver, B.C. V6C 3N6 Canada Tel: (604) 684-6264 Fax: (604) 684-6242

**Maximus and NFX Assays From Larder Lake Gold Project, Ontario
Reported on December 6, 2006**

Hole Numbers	From (m)	To (m)	Length (m) (¹)	Gold (g/t) (²)	Mineralization Type (³)
NFX06-09			<1 m@+1g/t	<3 gpt	
NFX06-10	142.10	142.65	0.55	4.70	Conglomerate
<i>And</i>	168.60	169.70	1.10	3.43	Conglomerate
<i>And</i>	430.50	436.10	5.60	2.32	Sediment
<i>including</i>	433.40	434.90	1.51	6.91	Sediment
<i>And</i>	516.95	519.55	2.60	3.41	Sediment
<i>including</i>	518.45	519.55	1.10	7.05	Sediment
<i>And</i>	534.05	534.60	0.55	5.89	Sediment
<i>And</i>	568.80	570.80	2.00	1.66	Sediment
<i>including</i>	568.80	569.50	0.70	4.30	Sediment
<i>And</i>	573.45	574.85	1.40	3.02	Sediment
<i>And</i>	759.15	760.30	1.15	3.25	Flow
NFX06-11*	71.00	75.70	4.70	5.49	Flow
<i>including</i>	72.15	74.65	2.50	8.78	Flow
NFX06-12	131.90	133.10	1.20	2.39	Flow
<i>including</i>	132.90	133.10	0.20	12.41	Flow
NFX06-13	278.55	279.95	1.4	5.45	Flow
<i>including</i>	278.55	279.30	0.75	9.79	Flow
NFX06-14				<1 gpt	
NFX06-15	258.90	266.00	7.10	1.32	Sediment/Flow
<i>including</i>	260.90	262.45	1.55	3.64	Sediment/Flow
<i>And</i>	489.55	494.85	5.30	1.77	Sediment/Flow
<i>including</i>	491.95	494.85	2.90	2.85	Sediment/Flow
NFX06-16	162.15	168.00	5.85	2.01	Sediment/Flow
<i>including</i>	165.85	166.75	0.90	5.17	Sediment/Flow
NFX06-17			<1m@+1g/t	<3gpt	
NFX 06-18	253.00	255.35	2.35	4.29	Flow
<i>Including</i>	254.45	255.35	0.90	6.45	Flow

Notes:

(1) Meters. Length is reported in meters of drilled core and is not necessarily the "true" width.

(2) Au g/t. Gold grades are reported in units of grams per tonne gold. All gold assays were performed by Expert Laboratories in Rouyn, QC using standard fire assaying protocols. Assay results from the 2006 drill program are considered accurate, precise and free of contamination as determined from assay results of quality control certified reference standards, field blank standards and duplicate samples submitted during the program. Core recovery generally exceeded 95%.

(3) Flow - contains abundant pyrite in altered volcanic rock. Carbonate - contains abundant ankerite, quartz veins, occasional visible gold, and only minor pyrite.

** Intersection from 71.00-75.70 meters with 5.49 gpt was reported on October 19, 2006.*